

# MANNING BUILDING SUPPLIES

## EXTERIOR PREHUNG DOOR UNIT SIZES

### UNIT SPECIFICATIONS:

DOOR: **STEEL OR FIBERGLASS**  
 UNDERSIZED DOOR: 1/4" WIDTH, 3/4" HEIGHT  
 JAMB: 1-1/4" X \_\_\_\_\_ WITH 1/2" MINIMUM STOP HEIGHT  
 SILL: ENDURA Z SERIES HIGH PERFORMANCE THRESHOLD  
 T-ASTRAGAL: ALUMINUM EXTRUDED ASTRAGAL REINFORCED  
 MULLION: 2-1/2" X 4-3/8" WITH 1/2" MIN STOP HEIGHT

ROUGH OPENING: WIDTH OF DOOR UNIT + 1/2"  
 HEIGHT OF DOOR UNIT + 1/4"

DOOR SIZE	UNIT WIDTH	UNIT HEIGHT INSWING	UNIT HEIGHT OUTSWING	UNIT HEIGHT ADA SILL
2-0 X 6-8	25-1/2"	82-1/16"	81-5/16"	81-1/8"
2-4 X 6-8	29-1/2"	82-1/16"	81-5/16"	81-1/8"
2-6 X 6-8	31-1/2"	82-1/16"	81-5/16"	81-1/8"
2-8 X 6-8	33-1/2"	82-1/16"	81-5/16"	81-1/8"
3-0 X 6-8	37-1/2"	82-1/16"	81-5/16"	81-1/8"
4-0 X 6-8	50"	82-1/16"	81-5/16"	81-1/8"
4-8 X 6-8	58"	82-1/16"	81-5/16"	81-1/8"
5-0 X 6-8	62"	82-1/16"	81-5/16"	81-1/8"
5-4 X 6-8	66"	82-1/16"	81-5/16"	81-1/8"
6-0 X 6-8	74"	82-1/16"	81-5/16"	81-1/8"
1-0 / 3-0 X 6-8	51-1/8"	82-1/16"	81-5/16"	81-1/8"
1-0 / 3-0 / 1-0 X 6-8	64-3/4"	82-1/16"	81-5/16"	81-1/8"
2-0 X 8-0	25-1/2"	98-1/16"	97-5/16"	97-1/8"
2-4 X 8-0	29-1/2"	98-1/16"	97-5/16"	97-1/8"
2-6 X 8-0	31-1/2"	98-1/16"	97-5/16"	97-1/8"
2-8 X 8-0	33-1/2"	98-1/16"	97-5/16"	97-1/8"
3-0 X 8-0	37-1/2"	98-1/16"	97-5/16"	97-1/8"
4-0 X 8-0	50"	98-1/16"	97-5/16"	97-1/8"
4-8 X 8-0	58"	98-1/16"	97-5/16"	97-1/8"
5-0 X 8-0	62"	98-1/16"	97-5/16"	97-1/8"
5-4 X 8-0	66"	98-1/16"	97-5/16"	97-1/8"
6-0 X 8-0	74"	98-1/16"	97-5/16"	97-1/8"
1-0 / 3-0 X 8-0	51-1/8"	98-1/16"	97-5/16"	97-1/8"
1-0 / 3-0 / 1-0 X 8-0	64-3/4"	98-1/16"	97-5/16"	97-1/8"